



## PANELS

### WC1250/CR COMPUTER ROOM PANEL:

The combination of composite wood core strength and steel outer sheets have made this a superior and flexible panel to meet every building requirement.

The WC Series CR panel combines a die cut galvanized steel top sheet and die cut formed bottom pan that are structurally bonded to the high density composite wood core with thermo setting adhesives. The surface covering is typically a high pressure laminate, or reinforced vinyl. All panels employ a mechanically locked trim. A positive plenum seal is created by identical panel squareness and a conductive vinyl stringer gasket.

### WC1250/GO GENERAL OFFICE PANEL:

The combination of a composite wood core and steel outer sheets provide superior acoustics.

The surface preparation is typically bare. Cornerlock design in conjunction with the high density composite wood core provides slab like underfoot performance.

PANEL TYPE	1250/CR IMPERIAL	1250/CR METRIC		1250/GO IMPERIAL	1250/GO METRIC
Concentrated Load*	1250 lbs.	5.57 kN		1250 lbs.	5.57 kN
Uniform Load**	300 lbs.	136 kg.		300 lbs.	136 kg.
Rolling Load ***	1250 lbs./800 lbs.	568 kg./362 kg.		1250 lbs./800 lbs.	568 kg./362 kg.
Minimum Ultimate Load*	2750 lbs.	1250 kg.		2500 lbs.	1136 kg.
Size	24" x 24"	600 mm x 600 mm		24" x 24"	600 mm x 600 mm
Finished Floor Heights	3" to 60"	75 mm to 1500 mm		2 1/2" to 24"	75 mm to 600 mm
Understructure	Bolted Stringer	Bolted Stringer		Cornerlock	Cornerlock
Floor Finishes	High pressure Laminate Conductive Vinyl	High pressure Laminate Conductive Vinyl		Free lay carpet tile Factory bonded carpet	Free lay carpet tile Factory bonded carpet

\* Measured on 1 sq.in. or 25 mm<sup>2</sup>.

\*\*Measured on 1 sq.ft. or 30 cm x 30 cm area.

\*\*\* 3" diameter (76mm) x 1 13/16" wide (46mm) wheel / 6" x 1 1/2" wide wheel. CISCA